

EA15 Series



| Part Number | EA1515 | EA1531 | EA1541 | EA1550 |
|---------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| Pixel pitch | 15.625/15.625mm | 15.625/31.25mm | 15.625/41.66mm | 15.625/50mm |
| Pixel configuration | 1R1G1B | 1R1G1B | 1R1G1B | 1R1G1B |
| Size of module | 10x1000/1500mm | 10x1000/1500mm | 10x1000/1500mm | 10x1000/1500mm |
| Resolution of module | 64X1 | 64X1 | 64X1 | 64X1 |
| Density | 4096 dots/m ² | 2048 dots/m ² | 1536 dots/m ² | 1280 dots/m ² |
| Cabinet material | Alu | Alu | Alu | Alu |
| Size of cabinet | 500x1000/1500mm | 500x1000/1500mm | 500x1000/1500mm | 500x1000/1500mm |
| Weight of cabinet | 8.2KG | 6.5KG | 5.5KG | 5KG |
| Transparency | 35% | 72% | 75% | 80% |
| Support hanging or not | Yes | Yes | Yes | Yes |
| Max power consumption | 690W/m ² | 500W/m ² | 450W/m ² | 430W/m ² |
| Average power consumption | 170W/m ² | 120W/m ² | 124W/m ² | 110W/m ² |
| Colors | 16.7M | 16.7M | 16.7M | 16.7M |
| Gray scale | 14Bits | 14Bits | 14Bits | 14Bits |
| Driving method | Static scanning | Static scanning | Static scanning | Static scanning |
| Refresh frequency | 2000Hz | 2000Hz | 2000Hz | 2000Hz |
| Brightness | 8000cd/m ² | 8500cd/m ² | 7500cd/m ² | 7000cd/m ² |
| IP grade | IP65/IP54 | IP65/IP54 | IP65/IP54 | IP65/IP54 |